

The rechargeable batteries are lead-lead dioxide systems. The dilute sulfuric acid electrolyte is absorbed by separators and plates and thus immobilized. Should the battery be accidentally overcharged producing hydrogen and oxygen, special one-way valves allow the gases to escape thus avoiding excessive pressure build-up. Otherwise, the battery is completely sealed and is, therefore, maintenance-free, leak proof and usable in any position.

General purpose application

LUXURY FM series are designed for general purpose applications, such as UPS, telecom, electrical utilities.

With 10 years design life, the batteries comply to the most popular international standards, such as IEC896-2, BS6290-4, Eurobat Guide.

The battery container and cover are available both in V0 class flame retardant ABS or HBO ABS plastics.

LUXURY SYSTEM Co., Ltd. has come to obtain wide recognition from customers all over the world. This is not only due to the fact that our products are featured by reliable stability in quality, but also because we attach great importance to our communication with customers and our perfect understanding of customers' requirements as well.

General Features

- Positive and negative plates in lead-calcium-tin alloy
- Stable Quality & High Reliability
- Sealed Construction
- Long Service Life
- Maintenance-Free Operation
- Low Pressure Venting System
- Low Self Discharge
- U. L. Component Recognition
- Six months shelf life at 20°C
- Design life 10 years



Dimensions and Weight

	SI Units	English Units
Length	520mm	20.5inch
Width	269mm	10.6inch
Height	203mm	8.0inch
Total Height	208mm	8.2inch
Approx. Weight	72.6Kg	160.1lbs

Performance Characteristics

- Nominal Voltage 12V
- Number of cell 6
- Nominal Capacity 77°F(25°C)
 - 10 hour rate (23.0A, 10.8V) 230Ah
 - 5 hour rate (44.6A, 10.5V) 223Ah
 - 1 hour rate (153A, 9.60V) 153Ah
- Internal Resistance
 - Fully Charged battery 77°F(25°C) ≤ 2.8mOhms
- Self-Discharge
 - 3% of capacity declined per month at 20°C(average)
- Operating Temperature Range
 - Discharge -20~60°C
 - Charge -10~60°C
 - Storage -20~60°C
- Max. Discharge Current 77°F(25°C) 1100A(5s)
- Short Circuit Current 4300A
- Charge Methods: Constant Voltage Charge 77°F(25°C)
 - Cycle use 2.40-2.45VPC
 - Maximum charging current 69A
 - Temperature compensation -30mV/°C
- Standby use 2.20-2.30VPC
 - Temperature compensation -20mV/°C

6FM230-X 12V 230Ah

Discharge Data

Constant Current Discharge Data (Amperes at 25°C)																								
End voltage volts/cell		15min	20min	25min	30min	35min	40min	45min	50min	55min	60min	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60V		371	307	268	242	216	197	182	170	161	153	111	89.6	76.9	68.5	54.0	45.4	38.0	32.8	28.9	25.8	23.4	20.3	10.4
1.65V		367	304	266	241	215	195	180	168	159	151	110	88.8	76.4	68.2	53.8	45.1	37.9	32.7	28.8	25.7	23.3	20.2	10.4
1.70V		365	302	265	240	214	194	179	167	158	150	109	88.3	76.0	67.8	53.5	44.9	37.7	32.5	28.6	25.6	23.2	20.1	10.3
1.75V		359	298	261	236	211	191	176	165	156	149	108	87.3	75.0	66.8	53.0	44.6	37.5	32.3	28.5	25.5	23.1	20.0	10.3
1.80V		348	290	256	233	208	189	174	164	155	148	107	87.0	74.7	66.5	52.6	44.3	37.2	32.1	28.3	25.4	23.0	19.9	10.2

Constant Power Discharge Data (Watts per cell at 25°C)																								
End voltage volts/cell		15min	20min	25min	30min	35min	40min	45min	50min	55min	60min	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60V		677	573	511	469	423	388	361	335	314	296	213	172	147	131	103	86.7	73.0	63.2	55.9	50.2	45.6	39.5	20.3
1.65V		673	570	507	466	420	386	359	333	312	294	212	171	146	130	103	86.4	72.8	63.0	55.7	50.0	45.4	39.4	20.3
1.70V		666	564	503	462	417	383	357	331	309	291	210	169	145	129	102	86.1	72.5	62.8	55.5	49.8	45.2	39.2	20.2
1.75V		658	558	499	459	415	381	355	328	306	288	208	168	144	128	101	85.8	72.2	62.5	55.2	49.6	45.0	39.0	20.1
1.80V		649	552	494	455	411	378	352	325	302	284	205	166	143	126	100	85.4	71.9	62.2	55.0	49.4	44.9	38.9	20.0

(Note) The above characteristics data are average values obtained within three charge/discharge cycles not the minimum values.
All data shall be changed without notice, LUXURY reserves the right to explain and update the information contained hereinto.



