

## SLCD20051 - 51.2V200Ah



### Product Features

### Residential Low voltage battery system

- High energy density, small size, light weight, no pollution;
- 0.75C rate charge/discharge;
- Match varied inverters;
- IP20 grade, suitable for indoor;
- 15 years design life, Stable performance, maintenance-free;



#### 2 Layers Safety Design

Much safer  
More reliable.



#### Smart management system

Available with Wifi,  
Bluetooth, LCD.



#### 0.75C Charge/Discharge

Efficient charging and  
discharging.



#### Single Management


Ultimate security and  
ultra-simple O&M.



### Multi-Function

Luxury lithium series batteries provide superior performance, capacities and reliability. Using state of high power cell technology, the lithium series is designed for environmentally sensitive areas that require super long cycle life capabilities.

Luxury lithium batteries are widely used in industrial, residential, commercial and private applications. The maintenance free construction and advanced design features makes the lithium series the definitive choice for a wide variety of markets. Like solar and renewable energy storage, electric vehicle, golf cart and industrial equipment, floor machines, forklifts, aerial lifts, and robotics; marine, RV, and no-idle solution; Mobility and Medical Equipment; Telecom, Broadband and Cable TV; UPS systems



#### Factory/Office Park/Hotel/Restaurant

Arbitraging from the TOU tariff, peak-load shifting



#### Mobile charger

Used as a backup power for household use



#### Off-grid

Multi-energy storage system with solar, diesel generator, wind turbine, etc.

## SLCD20051 - 51.2V200Ah

### Product Parameters

### Residential Low voltage battery system

Model	SLCD20051 - 51.2V200Ah
Battery Parameters	
Battery cell model	LiFePO <sub>4</sub> - 200Ah
Battery capacity	10.24kWh
Dimensions(LxWxH)	680*415*232mm
Weight	81
Terminal Type	T16/Plug
Terminal Torque	8.5N*M
Case Material	Steel
BMS build-in	Yes, software
Efficiency – round trip	> 99.5
Self Discharge per Month	< 3%
Max parallel connectors	15
Series connections	1
Cycle life (1C, 25°C@100% DOD)	> 6000
Discharge Temperature	-23~65°C
Charge Temperature	-3~65°C
Storage Temperature	-20~45°C
Bluetooth(App)	Optional
LCD Screen	Optional
IR ( Internal resistance , 20 )	14.8mΩ @ 50% SOC
Voltage Window	44.8~57.6V
Recommend Charge Voltage	57V
Max Charge Voltage	59V
Recommend Charge current	20A
Max continuous charge current	150A
Recommend Discharge voltage	46V
Max Discharging Voltage	44.8V
Max Continuous Discharge current	100A
Peak Discharge Current	120A
Communication	RS485,Can

\* The system will be derated when the ambient temperature exceeds 45°C.

\*\* The system will be derated when the altitude is between 2000 and 3000m.

### Certifications

**System:** CE(IEC61000,IEC62619,IEC62477),UN3480, UKCA ;

**Cell:** IEC 62619, UL1973, UL9540A;

**Pack:** UN38.3;

**Note:** Product specifications are subject to change without any prior notice as per regular modifications made by company.



### Residential Low voltage battery system


#### Constant Current Discharge Data (Amperes @ 25°C)

Discharge Time	1h	2h	3h	4h	5h	10h	20h
Cut off voltage (42.0V)	200A	100A	66A	50A	40A	20A	10A


#### Constant Current Discharge Data (Amperes @ 25°C)

Discharge Time	1h	2h	3h	4h	5h	10h	20h
Cut off voltage (42.0V)	10240W	5120W	3412W	2560W	2048W	1024W	512W


Discharge characteristics (25°C)




Different temperature Discharge curve (0.5C)



Discharge DOD discharge cycle life curve (0.2C, 25°C)



State of charge curve (0.5C, 25°C)



Note 1: Please always refer to the latest edition of our technical manual that published on our website to ensure safe and efficient operation.

Note 2: When make parallel connection, please full discharge batteries, then recharge after parallel connected; when series connect, please keep batteries with same remain capacity.